



2~5A

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated

| 编号 | 尺寸 (mm) | |
|-----------|---------|-------|
| | A | B |
| A2508-02A | 2.50 | 7.50 |
| A2508-03A | 5.00 | 10.00 |
| A2508-04A | 7.50 | 12.50 |
| A2508-05A | 10.00 | 15.00 |
| A2508-06A | 12.50 | 17.50 |
| A2508-07A | 15.00 | 20.00 |
| A2508-08A | 17.50 | 22.50 |
| A2508-09A | 20.00 | 25.00 |
| A2508-10A | 22.50 | 27.50 |
| A2508-11A | 25.00 | 30.00 |
| A2508-12A | 27.50 | 32.50 |
| A2508-13A | 30.00 | 35.00 |
| A2508-14A | 32.50 | 37.50 |
| A2508-15A | 35.00 | 40.00 |
| A2508-20A | 47.50 | 52.50 |

PCB LAYOUT

| | | | | | | | | | |
|-------------------|------------|---------|------------|----|--------------|----------------|---------------|---------------------|-----|
| GENERAL TOLERANCE | | 制图 | 钱岳生 | | 料号 | A2508-nA | | 版本 | A |
| X.±0.25 | X.*±2' | DRAWING | 2013、07、01 | | PART NO. | XA单排直针 | | REV. | 1/1 |
| .X±0.20 | .X*±1' | 审核 | 张名 | | TITLE | WAFER DIP TYPE | | SHEET | 1/1 |
| .XX±0.15 | .XX*±0.5' | CHECK | 2013、07、03 | | CUTM. NO. | 深圳市金航标电子有限公司 | | www.kinghelm.com.cn | |
| .XXX±0.10 | .XXX*±0.5' | 核准 | 张名 | | KH-A2508-05A | | 0755-28190160 | | |
| APPROVAL | 2013、07、03 | 单位 | MM | 比例 | 1:1 | | | | |