



**PCB LAYOUT**

**SPECIFICATIONS**

- 1、 Current Rating: 2A AC, DC
- 2、 Voltage Rating: 250V AC, DC
- 3、 Temperatuer Range: -25℃~+85℃
- 4、 Contact Resistance: 20mΩ Max
- 5、 Insulation Resistance: 1000MΩ Min
- 6、 Withstanding Voltang: 800V AC/minute
- 7、 Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2001-02AW	2.00	6.00
A2001-03AW	4.00	8.00
A2001-04AW	6.00	10.00
A2001-05AW	8.00	12.00
A2001-06AW	10.00	14.00
A2001-07AW	12.00	16.00
A2001-08AW	14.00	18.00
A2001-09AW	16.00	20.00
A2001-10AW	18.00	22.00
A2001-11AW	20.00	24.00
A2001-12AW	22.00	26.00
A2001-16AW	30.00	34.00

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	贺骏驹		料号 PART NO.	A2001-NAW		版本 REV.	A			
			X.±0.25	X.'±2'		审核 CHECK	赖积任		品名 TITLE	PH弯针		页次 SHEET	1/1		
			X.±0.20	X.'±1'			核准 APPROVAL	2013、07、03		客户料号 CUTM. NO.	WAFER DIP TYPE				
			.XX±0.15	.XX'±0.5'		2013、07、05		张松强			深圳市金航标电子有限公司			WWW.BDS666.COM	
			.XXX±0.10	.XXX'±0.5'				单位 UNITS	MM						