



PCB LAYOUT 图仅供参考

料号: B000166-0100-XXX-XX-0X

- "1"表示PBT
- "0"表示黑色
- "1"表示端子镀金 G/F
- R= (卷装)
- H表示无卤
- 00: 有LOGO
- 01: 没LOGO

Note:

1.Material:

- 1.1 Housing: PA9T
- 1.2 Contact: C5191,t=0.20mm
- 1.3 Shell: Kirsite

2.ELECTRICAL:

- 2-1: CURRENT RATING:
VBUS AND GND CONTACTS RATED AT 1.25A
PARALLELED FOR A TOTAL OF 5A;
- 2-2: INITIAL CONTACT RESISTANCE : 40 MEGOHMS
- 2-3: DIELECTRIC WITHSTANDING VOLTAGE:
100V AC MIN;

3: MECHANICAL CHARACTERISTICS:

- 3-1: MATING FORCE: 5~20N
- 3-2: UNMATING FORCE: 8~20N (INITIAL),
6~20N (AFTER 10000 CYCLES)
- 3-3: FREQUENCY: 200±50 CYCLES /HOUR, 10000
CYCLES
- 3-4: OPERATING TEMPERATURE ; -40~80°.

ALL MATERIAL MEET THE FORMAN'S SPBC: ENVIRONMENT-RELATED SUBSTANCES MANAGEMENT TECHNICAL STANDARD

深圳市金航标电子有限公司

WWW.BDS666.COM

KH-TYPE-C-L-FS-6P-STM

0755-83044319

■ RoHS TOLERANCE (UNLESS SPECIFIED) .0±0.30 .00±0.20 .000±0.10	■ HF 0.±10" .0"±8" .00"±5"	品名 TITLE: 防水TYPE-C 6P 立贴带贴片脚母座		比例	图号
		SCALE	1:1	DWG NO.:	B000166-0100
料号 ITEM NO: B00166-0100-XXX-XX-0X		张数	1/1		
审核 APPROVE BY: 设计 DESIGN BY: L S W		版本	1		
		REV.		UNITS:	

TABLE B

A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2
PIN	SIGNAL NAME	PIN	SIGNAL NAME